

# RT SERIES

ENGINE POWERED ROUGH TERRAIN  
SCISSOR LIFTS

## Performance

• Platform Height—Elevated			
RT2669	26'2"	8 m	
RT3369	32'8"	10 m	
RT4069	40'3"	12.3 m	
RT4769	7'	14.3 m	
• Platform Height — Lowered			
RT2669	4'3"	1.3 m	
RT3369	4'9"	1.5 m	
RT4069	4'10"	1.5 m	
RT4769	5'4"	1.6 m	
• Platform Capacity (Single Extension)			
RT2669	1,500 lb	680 kg	
RT3369	1,000 lb	454 kg	
RT4069	800 lb	363 kg	
RT4769	800 lb	363 kg	
- Capacity on Deck Extension	300 lb	136 kg	
• No. Occupants (Indoor/Outdoor)			
RT2669	4/4		
RT3369	4/2		
RT4069	3/2		
RT4769	3/2		
• Lift/Lower Time			
RT2669	36/28 seconds		
RT3369	42/33 seconds		
RT4069	69/46 seconds		
RT4769	81/55 seconds		
• Maximum Drive Height			
• Weight (single extension w/out leveling jacks)*			
RT2669	8,058 lb	3,655 kg	
RT3369	8,856 lb	4,017 kg	
RT4069	10,536 lb	4,779 kg	
RT4769	13,635 lb	6,185 kg	
• Drive Speed—Lowered	3.5 mph	5.6 km/h	
• Drive Speed—Elevated	0.5 mph	0.8 km/h	
• Max Tilt Rating (side-to-side)	2.5 Degrees		
• Max Tilt Rating (fore & aft)	3 Degrees		
• Gradeability			
RT2669	40%		
RT3369	40%		
RT4069	35%		
RT4769	30%		
• Turning Radius (Inside)	83"	2.1 m	
• Turning Radius (Outside)	175"	4.44 m	

\* Certain options or country standards will increase weight.  
\*\* RT4769 Includes a Push-Button Manual Descent System

## Standard Specifications

• Tire Size	26 x 12 Foam Filled
• Diesel Engine	Kubota D1305-E4B 24.8 hp (18.5 kw)
• Fuel Tank Capacity	10 gal (38L)
• Drive	2WD Hydrostatic
• Hydraulic Reservoir	13.2 gal (50 L)

## Preliminary version



## Standard Features

- 42 in/1.06 m Roll-out Deck Extension
- Nickel Plated Pins, Yellow Zinc-Chromate
- Plated Fasteners
- Pin-Less Fold Down Rail System
- Platform Control Box with LCD Display, USB Charger and Phone Holster
- Self-Closing Gate
- Full Time Traction Control
- Lubrication-Free Scissor Arm Bushings
- Manual Descent Pull Cable \*\*
- Oscillating Front Axle
- Scissor Maintenance Prop
- Tie Down Lugs
- 26 x 12 Foam Filled Lug Tread Tires
- 220V-AC Receptacle In Platform
- All Motion Alarm
- Horn
- Hourmeter
- Proportional Lift and Drive
- Pin-based Load Sensing System
- Telematics-Ready Harness
- LCD Display with LiftSense System
- Fold Down Rails
- EN280 Compliant
- Moveable, Removable Platform Control Box

## Accessories & Options

- Hydraulic Leveling Jacks (Auto Level)
- Hydraulic Oil Cooler (Excludes RT4769)
- 26 x 12 Foam Filled Non-Marking Tires
- Flashing Amber Beacon - LED
- Dual Flashing Amber Beacons - LED
- White Noise Backup Alarm
- Special Hydraulic Fluids
- Special Paint
- ClearSky™
- Operator Access Control
- QuikLevel Advanced
- Heavy Duty Pipe Racks
- 4 Wheel drive